Yuasa Technisches Datenblatt

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3012 - YBX3000 SMF Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	52Ah
Kaltstartstrom (A) EN1	450A



Abmessungen

Länge	207mm
Breite	175mm
Höhe	190mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	13.3kg

Gehäuseeigenschaften


Gehäusetyp	L1 DIN
Batteriehalter	B13/B14
Ladezustandsanzeige	✔
Tragegriffe	✔
Entgasung	✔
Deckeltyp	SMF doppelwandige Deckelkonstruktion

Technologie


Flammschutz	✔
Technologie	Ca/Ca
Adskiller	PE
VDA Überschlagtest	✔
Empfohlener Ladestrom	3A
Performance Marking	W3-C2-V2-E1

Anschlusspol Typ


T1
Standard DIN Post



Zellenanordnung



Batteriehalter



Datenblatt erstellt am 28/03/2024 - E&EO

Yuasa Technical Data Sheet

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3012 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	52Ah
Cold Cranking Amps (EN1)	450A



Dimensions

Length	207mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	13.3kg

Container Features


Case Type	L1 DIN
Hold Down	B13/B14
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	3A
Performance Marking	W3-C2-V2-E1

Terminal Type


T1
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 28/03/2024 – E&OE