Yuasa Technisches Datenblatt

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3053 - YBX3000 SMF Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	45Ah
Kaltstartstrom (A) EN1	400A



Abmessungen

Länge	238mm
Breite	129mm
Höhe	225mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	12.4kg

Gehäuseeigenschaften


Gehäusetyp	JIS B24
Batteriehalter	N
Ladezustandsanzeige	✔
Tragegriffe	✔
Entgasung	✔
Deckeltyp	SMF doppelwandige Deckelkonstruktion

Technologie


Flammschutz	✔
Technologie	Ca/Ca
Adskiller	PE
VDA Überschlagtest	✔
Empfohlener Ladestrom	3A
Performance Marking	W3-C2-V2-E1

Anschlusspol Typ

T1/T3
Standard DIN Post



Zellenanordnung



Batteriehalter



Datenblatt erstellt am 29/03/2024 - E&EO

Yuasa Technical Data Sheet

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX3053 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	400A



Dimensions

Length	238mm
Width	129mm
Height	225mm

Weights & Measures

Mean Weight with Acid	12.4kg

Container Features


Case Type	JIS B24
Hold Down	N
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	3A
Performance Marking	W3-C2-V2-E1

Terminal Type

T1/T3
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 29/03/2024 – E&OE