Yuasa Technisches Datenblatt

Yuasa YBX3111 - YBX3000 SMF Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	50Ah
Kaltstartstrom (A) EN1	530A



Abmessungen

Länge	236mm
Breite	182mm
Höhe	178mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	12.9kg

Gehäuseeigenschaften


Gehäusetyp	US Gp 58
Batteriehalter	B1
Ladezustandsanzeige	✔
Tragegriffe	✔
Entgasung	✔
Deckeltyp	SMF doppelwandige Deckelkonstruktion

Technologie


Flammschutz	✔
Technologie	Ca/Ca
Adskiller	PE
VDA Überschlagtest	✔
Empfohlener Ladestrom	4A
Performance Marking	W4-C2-V3-E1

Anschlusspol Typ


T1
Standard DIN Post



Zellenanordnung



Batteriehalter



Datenblatt erstellt am 28/03/2024 - E&EO

Yuasa Technical Data Sheet

Yuasa YBX3111 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	50Ah
Cold Cranking Amps (EN1)	530A



Dimensions

Length	236mm
Width	182mm
Height	178mm

Weights & Measures

Mean Weight with Acid	12.9kg

Container Features


Case Type	US Gp 58
Hold Down	B1
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	4A
Performance Marking	W4-C2-V3-E1

Terminal Type


T1
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 28/03/2024 – E&OE