



Yuasa Technisches Datenblatt

Yuasa YBX9027 - YBX9000 AGM Start Stop Plus Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	60Ah
Kaltstartstrom (A) EN1	640A

Abmessungen

Länge	242mm
Breite	175mm
Höhe	190mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	17.7kg
--	--------



Gehäuseeigenschaften

Gehäusotyp	L2 DIN AGM
Batteriehalter	B3
Tragegriffe	✓
Entgasung	✓
Semi Traktionseigenschaften	✓
Deckeltyp	VRLA


Technologie

Flammschutz Technologie	✓
Adskiller	Ca/Ca VRLA
VDA Überschlagentest	AGMSORTIMENT
Empfohlener Ladestrom	✓
Performance Marking	4A
	W5-C2-V3-M3

Anschlusspol Typ

T1


Standard DIN Post



Positive Terminal

Negative Terminal

Zellenanordnung



Batteriehalter

Datenblatt erstellt am 28/03/2023 - E&EO



Yuasa Technical Data Sheet

Yuasa YBX9027 - YBX9000 AGM Start Stop Plus Batteries

Performance

Voltage	12V
Capacity (20-hour)	60Ah
Cold Cranking Amps (EN1)	640A

Dimensions

Length	242mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	17.7kg
-----------------------	--------

Container Features

Case Type	L2 DIN AGM
Hold Down	B3
Handles	✓
End Venting	✓
Semi-Traction Features	✓
Lid Type	VRLA

Technology

Flame Arrestor Technology	✓
Separator	Ca/Ca VRLA AGM
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W5-C2-V3-M3

Terminal Type

Cell Assembly Layout

Battery Hold-down

Data Sheet generated on 28/03/2023 – E&OE

