Yuasa Technisches Datenblatt

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX9096 - YBX9000 AGM Start Stop Plus Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	70Ah
Kaltstartstrom (A) EN1	760A



Abmessungen

Länge	278mm
Breite	175mm
Höhe	190mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	20.5kg

Gehäuseeigenschaften


Gehäusetyp	L3 DIN AGM
Batteriehalter	B3
Tragegriffe	✔
Entgasung	✔
Semi Traktionseigenschaften	✔
Deckeltyp	VRLA

Technologie


Flammschutz	✔
Technologie	Ca/Ca VRLA
Adskiller	AGMSORTIMENT
VDA Überschlagtest	✔
Empfohlener Ladestrom	4A
Performance Marking	W5-C2-V3-M3

Anschlusspol Typ


T1
Standard DIN Post



Zellenanordnung



Batteriehalter



Datenblatt erstellt am 29/03/2024 - E&EO

Yuasa Technical Data Sheet

* Due to unprecedented demand following the easing of COVID-19 lockdown measures, this product may be supplied without a state of charge indicator and not conform to the level of roll over protection advertised. Product performance and quality are not affected by this. Please check battery labels for specification details.

Yuasa YBX9096 - YBX9000 AGM Start Stop Plus Batteries

Performance

Voltage	12V
Capacity (20-hour)	70Ah
Cold Cranking Amps (EN1)	760A



Dimensions

Length	278mm
Width	175mm
Height	190mm

Weights & Measures

Mean Weight with Acid	20.5kg

Container Features


Case Type	L3 DIN AGM
Hold Down	B3
Handles	✔
End Venting	✔
Semi-Traction Features	✔
Lid Type	VRLA

Technology


Flame Arrestor	✔
Technology	Ca/Ca VRLA
Separator	AGM
VDA Roll Over Test	✔
Recommended Charge Rate	4A
Performance Marking	W5-C2-V3-M3

Terminal Type


T1
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 29/03/2024 – E&OE